



TSM-R



Shredders equipped with **REVERSIBLE THREE-POINT LINKAGE**, hammers or universal blades for mid-size pruning of up to 8 cm diameter, grass lawns, vine runners, hazel groves, orchards, kiwi, etc.








Features: possibility of attachment to 540 and 1000 rpm PTO by inverting the pulleys position, rounded external side without projecting parts that may damage the plants, low power absorption, oversized transmission and three-point linkage with mechanical or hydraulic shift.



TSM-R



DATI TECNICI SPECIFICATIONS - CARACTERISTIQUES TECHNIQUES - TECHNISCHE DATEN - DATOS TÉCNICOS

MODELLO MODEL MODELE TYP MODELO									
	Lavoro Working width Largeur de coupe Arbeitsbreite Trabajo cm	Ingombro Overall width Largeur hors tout Gesamtbreite Ancho total cm	Spostamento Shift Déplacement Verschiebung Desplazamiento mm	kW	HP	Kg	lbs	#	#
TSM-R 100	100	115	365/645 620/380	15 - 22	20 - 30	280	616	8	16
TSM-R 110	110	125	365/745 665/480	18 - 22	25 - 30	290	638	8	16
TSM-R 120	120	135	365/845 665/580	18 - 26	25 - 35	300	660	10	20
TSM-R 140	140	155	365/1045 665/780	30 - 33	40 - 45	340	748	12	24
TSM-R 160	160	175	365/1245 665/980	33 - 41	45 - 55	380	836	14	28
TSM-R 180	180	195	365/1445 665/1180	37 - 45	50 - 60	420	924	14	28